

## **SOLIDWORKS Plastics Product Matrix**

	SOLIDWORKS Plastics Standard	SOLIDWORKS Plastics Professional	SOLIDWORKS Plastics Premium
Ease of Use	✓	$\checkmark$	$\checkmark$
SOLIDWORKS Plastics is fully embedded in SOLIDWORKS 3D CAD for ease of interface (UI) as SOLIDWORKS in toolbars, menus, and context-sensitive right in tutorials and searchable online help aid learning and troubleshooting.			
Design Data Reuse	<b>√</b>	$\checkmark$	✓
SOLIDWORKS Plastics supports SOLIDWORKS materials and configurations for configurations.	or easy analysis o	f multiple loads a	and product
Materials Database	<b>√</b>	$\checkmark$	✓
With 4,000+ commercial thermoplastic grades, you can browse and select the material library.	ne desired from t	he customizable	built-in
Meshing	<b>√</b>	<b>√</b>	✓
SOLIDWORKS Plastics includes these meshing features:			
<ul> <li>Wizard for mesh generation and analysis setup</li> <li>Automatic Mesh</li> <li>Local Mesh Refinement</li> <li>Global Mesh Refinement</li> <li>Boundary Mesh (Shell)</li> <li>Solid 3D mesh</li> </ul>			
Parallel Computing (Multi-Core)	✓	<b>√</b>	$\checkmark$
The 3D Solver benefits from a multi-core CPU (multiple threads).			
Filling Phase (1st Stage Injection)	<b>√</b>	$\checkmark$	✓
Predicts how material fills the cavity. Results include distributions of pressur detection of potential short shots and weld lines.	e and temperatu	re within the cav	vity, and
Automatic Gate Location(s)	<b>√</b>	✓	✓
Defines up to 10 injection locations on the part cavity automatically. SOLIDV part based on the geometry and optimized balanced fill pattern.	VORKS Plastics ac	lds injection loca	itions onto the
Instantaneous Fill Time Plot	✓	✓	$\checkmark$
Predicts the plastic flow pattern through the cavity at the end of fill.			
Sink Mark Analysis	<b>√</b>	$\checkmark$	$\checkmark$

Predicts the depth of sink marks after the part has been ejected and cooled to room temperature.

	SOLIDWORKS Plastics Standard	SOLIDWORKS Plastics Professional	SOLIDWORKS Plastics Premium
eDrawings Support	<b>√</b>	<b>√</b>	<b>√</b>
Results can be exported to eDrawing®			
Fill Time	<b>√</b>	$\checkmark$	<b>√</b>
Time needed to fill the whole mold.			
Ease of Fill	<b>√</b>	<b>√</b>	<b>√</b>
Displays the quality of the injection process with 'confidence of fill' legend.			
Results Adviser	<b>√</b>	✓	<b>√</b>
	ŕ	ŕ	·
User assistant for interpreting results.			
Nominal Wall Thickness Adviser	<b>√</b>	✓	<b>V</b>
Analyzes the part thickness and locates the high thickness ratio.			
Pressure at End of Fill	<b>√</b>	<b>√</b>	<b>√</b>
Displays the maximum pressure to fill the cavity.			
Flow Front Temperature	✓	✓	<b>√</b>
Displays the melt front temperature history.			
Temperature at End of Fill	<b>√</b>	<b>√</b>	✓
Displays the Cavity Temperature field at the end of fill.			,
Shear Rate	<b>√</b>	<b>√</b>	<b>√</b>
Displays the shear rate reached at the end of fill to check the injection proc	ess quality.		
Cooling Time	✓	✓	<b>√</b>
Estimates cooling time at fill time analysis.			
Weld Lines  Displays weld lines formed at locations of the part where two (or multiple)	√ malt frants maat	<b>√</b>	<b>√</b>
Air Traps	ment monts meet √	√	<b>√</b>
Shows the location where high pressure air may be trapped inside the cavit			
Sink Marks	√ ·	✓	✓
Displays the location of sink marks.			
Frozen Layer Fraction at End of Fill	✓	✓	✓
Displays the fraction of frozen material into the part at end of fill.			
Clamp Force	<b>√</b>	$\checkmark$	✓
Displays the minimum clamp force for the current injection process.		/	
Cycle Time  Displays the cycle time for the current injection process.	•	r	V
Symmetry Analysis		✓	<b>√</b>
Avoid simulating both cavities in a symmetrical mold layout, saving comput	er time for the si	mulation.	
Packing Phase (2nd Stage Injection)		✓	✓
Evaluates the material freezing process in the cavity. Predicts the temperat		ot spots, gate fr	eeze, and cycle
time. Distributions of pressure, stress, and shrinkage results are also available.	JIE.	_	<b>√</b>
Runner Balancing		V	V

Determines the runner parameters to balance filling between parts.		
Runner Design Wizard	✓	✓
Automates the process of creating common flow control devices and components such as spru	ies, runners, an	d gates.
Sprues and Runners	✓	✓
Quickly and easily simulate the impact of the sprues and runners layout.		
Hot & Cold Runners	✓	✓
Hot runners are initially filled with hot polymer at the start of the filling simulation.		
Multi-Cavity Molds	✓	$\checkmark$
Simulates multiple cavities of the same part in the same mold.		
Family Molds	✓	$\checkmark$
Simulates a set of different cavities parts in the same mold.		
Mold Inserts	✓	✓
Include the impact of mold inserts on the simulation		
Volumetric Shrinkage	✓	<b>√</b>
Displays volumetric shrinkage distribution at the end of fill or pack.		
Density at End of Pack	✓	$\checkmark$
Displays density distribution at post-filling end to check the pack phase quality.		
Exports STL, NASTRAN	✓	✓
Enables you to export part geometry in STL or NASTRAN formats		
Export with Mechanical Properties ABAQUS®, ANSYS, DigiMat®	✓	✓
Exports mesh, residual stress, fiber orientation and material data to run non-linear analysis.		
Cooling Lines		✓
Simulates the coolant flowing inside for the mold cooling analysis.		
Baffles & Bubblers		✓
Specific cooling line for narrow channel into the cavity.		
Conformal Cooling Channels		✓
Cooling passageway follows the shape or profile of the mold core or cavity to perform rapid un	niform cooling p	rocess.
Runner Domain Category		<b>√</b>
Domain category assigned to the runner allows easy selection for runner's conditions.		
Sink Mark Profiles		✓
Displays the location of sink marks and their depth.		
Mold Temperature at Cooling End		✓
Displays the mold temperature distribution at cooling end.		
Displacement Due to Residual Stress		✓
Displays the displacement distribution due to in-mold stress.		



SOLIDWORKS SOLIDWORKS

**Plastics** 

Professional

**Plastics** 

Premium

**Plastics** 

Standard